

Quick Start Installation Guide

Thank you very much for purchasing the TwEECer, you now have the most powerful tuning tool available for Ford EEC-IV & EEC-V processors. The software for the TwEECer is ONLY available via the web, there is no CD-ROM disc that ships with the product.

Your TwEECer should have shipped with the following items:

- TwEECer module
- TwEECer switch
- USB cable
- Switch cable (phone cable)
- TwEECer sticker
- Quick Start Guide

You should not install the TwEECer in the vehicle until you have a PC that can communicate with the device properly. The TwEECer ships with no calibrations (blank) and is not capable of operating your vehicle until at least the stock calibration has been written to one of the 4 custom positions.

Please do NOT connect your TwEECer to the EEC or your PC until you have followed the steps below and are ready to install the USB driver for the TwEECer.

- Visit www.tweecer.com on the internet
- Click on the Downloads menu option
- Download **Borland Database Engine (BDE)**
- Download **RT130A9**
- Download **RT130B3**
- Run BDEInst.exe and follow the prompts
*** The BDE is circa 1997 when Hard disks averaged in the 2-10Gb range, it will report that there is not enough space on most drives manufactured after 1998. You can ignore this and any other error reported during the install of BDE.
- Unzip and run RT130A9 and follow the prompts
- Unzip and run RT130B3 and follow the prompts

You are now ready to install the driver for the TwEECer, these steps and much more are detailed the Getting Started.PDF (Manual) and should be used for any further procedures.

Windows Vista Install Notes

After installing the software and before connecting the TwEECer, you should change the Windows Emulation option on the CalEdit and CalCon icon properties. They should be set to Windows XP compatibility mode.

